

MORE



Avorio


Bianco

Grigio



Perla

Tortora



V3 Moderate Variation

Regularity Characteristics

| Technical Features | Norms | Required Standards | Value |
|-----------------------|-------------|--------------------|--------------|
| Length & Width | ISO 10545-2 | ± 0,6% | Suitable for |
| Thickness | | ± 5% | Suitable for |
| Straightness of Sides | | ± 0,5% | Suitable for |
| Rectangularity | | ± 0,6% | Suitable for |
| Surface Flatness | | ± 0,5% | Suitable for |

Structural Characteristics

| Technical Features | Norms | Required Standards | Value |
|--------------------|-------------|--------------------|--------------|
| Water Absorption | ISO 10545-3 | ≤ 0,5% | Suitable for |

Bulk Mechanical Characteristics

| Technical Features | Norms | Required Standards | Value |
|--------------------|-------------|--------------------------|--------------|
| Bending Strength | ISO 10545-4 | R ≥ 35 N/mm ² | Suitable for |

Surface Mechanical Characteristics

| Technical Features | Norms | Required Standards | Value |
|-----------------------------|-------------|-----------------------|--------------|
| Mohs Hardness | EN 101 | ≥ 6 | 8 |
| Resistance to Deep Abrasion | ISO 10545-6 | ≤ 175 mm ³ | Suitable for |

Thermal and Hygrometric Characteristics

| Technical Features | Norms | Required Standards | Value |
|---|--------------|---|--------------------------------------|
| Coefficient of Thermal Linear Expansion | ISO 10545-8 | Test Method Available | -7x10 ⁻⁶ °C ⁻¹ |
| Thermal Shock Resistance | ISO 10545-9 | Test Method Available | Suitable for |
| Resistance to Frost | ISO 10545-12 | Required | Suitable for |
| Color Resistance to Light | DIN 51094 | The Sample Must Show No Noticable Colour Change | Suitable for |

Safety Characteristics

| Technical Features | Norms | Required Standards | Value |
|--------------------------------|----------------------------|------------------------|----------------------------------|
| Dynamic Friction Coefficient | ANSI 137.1-2012 (D.C.O.F.) | ≥ 0,42 WET | ≥ 0,49 WET |
| Static Coefficient of Friction | ASTM C 1028 (S.C.O.F.) | ≥ 0,6 DRY ≥ 0,6 WET | Not Provided By the Manufacturer |
| Non-Slip Classification | DIN 51130 | 9 ≤ R ≤ 13 | R10 |

Chemical Characteristics

| Technical Features | Norms | Required Standards | Value |
|------------------------|--------------|---------------------------------------|--------------|
| Chemical Resistance | ISO 10545-13 | According to Builder's Specifications | Suitable for |
| Resistance to Staining | ISO 10545-14 | No Alteration | Suitable for |

Stocked Sizes (Nominal)

| Dimensions | Available Colors |
|-----------------------------------|---|
| 12"x24"x9.5mm Field Tile | Avorio, Bianco, Grigio, Perla, Tortora (Natural Rectified, Muretto, Velvet, Design) |
| 18"x36"x11mm Field Tile | Avorio, Bianco, Grigio, Perla, Tortora (Natural Rectified) |
| 2.5"x2.5" on 12"x12"x9.5mm Mosaic | Avorio, Bianco, Grigio, Perla, Tortora (Natural Rectified) |
| 3"x24"x9.5mm Bullnose | Avorio, Bianco, Grigio, Perla, Tortora (Natural Rectified) |

Special Order Sizes* (Nominal)

| Dimensions | Available Colors |
|-------------------------------------|--|
| 80x80 - 31.5"x31.5"x11mm Field Tile | Avorio, Bianco, Grigio, Perla, Tortora (Natural Rectified, Levigato Rectified) |
| 60x60 - 24"x24"x9.5mm Field Tile | Avorio, Bianco, Grigio, Perla, Tortora (Natural Rectified, Levigato Rectified) |
| 45x90 - 18"x36"x11mm Field Tile | Avorio, Bianco, Grigio, Perla, Tortora (Levigato Rectified) |
| 30x60 - 12"x24"x9.5mm Field Tile | Avorio, Bianco, Grigio, Perla, Tortora (Levigato Rectified) |
| 10x30 - 4"x12"x9.5mm Field Tile | Avorio, Bianco, Grigio, Perla, Tortora (Natural Rectified) |
| 7x90 - 3.13"x31.5"x11mm Bullnose | Avorio, Bianco, Grigio, Perla, Tortora (Natural Rectified, Levigato Rectified) |
| 7x90 - 3"x36"x11mm Bullnose | Avorio, Bianco, Grigio, Perla, Tortora (Natural Rectified) |
| 30x60 - 12"x24"x9.5mm Gradino | Avorio, Bianco, Grigio, Perla, Tortora (Natural Rectified) |

* 12 - 14 Week Lead Time

Recycled Content

| |
|------------------------------|
| Not Provided By Manufacturer |
|------------------------------|