




COAL




DUST



MUD



WHITE



V2 Slight Variation (Raw-White Only)
V3 Moderate Variation

Regularity Characteristics

Technical Features	Norms	Required Standards	Value	
		N ≥ 15cm	Matte	Stattuario
Length & Width	ISO 10545-2	±0,6% (±2 mm)	± 0,15%	± 0,15%
Thickness		±5% (±0,5 mm)	±5%	±5%
Straightness of Sides		±0,5% (±1,5 mm)	± 0,1%	± 0,1%
Rectangularity		±0,5% (±2 mm)	± 0,2%	± 0,2%
Surface Flatness		±0,5% (±2mm)	± 0,35%	± 0,35%

Structural Characteristics

Technical Features	Norms	Required Standards	Value	
		N ≥ 15cm	Matte	Stattuario
Water Absorption	ISO 10545-3	E < 0,5%	0,08%	

Bulk Mechanical Characteristics

Technical Features	Norms	Required Standards	Value	
		N ≥ 15cm	Matte	Stattuario
Breaking Strength	ISO 10545-4	≥ 1300 N	3200 N	
Modulus of Rupture		> 35 N/mm ²	50 N/mm ²	

Surface Mechanical Characteristics

Technical Features	Norms	Required Standards	Value	
		N ≥ 15cm	Matte	Stattuario
Resistance to Deep Abrasion	ISO 10545-6	See Manufacturer's Declaration	140mm ³	

Thermal and Hygrometric Characteristics

Technical Features	Norms	Required Standards	Value	
		N ≥ 15cm	Matte	Stattuario
Thermal Shock Resistance	ISO 10545-9	Available Testing Method	Resistant	
Resistance to Frost	ISO 10545-12	Required		

Safety Characteristics

Technical Features	Norms	Required Standards	Value	
		N ≥ 15cm	Matte	Stattuario
Dynamic Friction Coefficient	ANSI A 137.1 2012 (D.C.O.F)	> 0,42 WET	> 0,42 WET	
Pendulum Friction Test	BS 7976	-	> 36 WET	
Non-Slip Classification	DIN 51130	-	R10	R11
Slip Resistance	DIN 51097	-	A + B	A + B

Chemical Characteristics

Technical Features	Norms	Required Standards	Value	
		N ≥ 15cm	Matte	Stattuario
Resistance to Household Chemicals and Swimming Pool Salts	ISO 10545-13	Min. B	UA	
Resistance to low Concentrations of Acids and Alkalis		See Manufacturer's Declaration	ULA	
Resistance to High Concentrations of Acids and Alkalis		See Manufacturer's Declaration	UHA	
Resistance to Staining	ISO 10545-14	Available Testing Method	Class 4	

Stocked Sizes (Nominal)

Dimensions	Available Colors
12"x24"x10mm Field Tile	Raw-Coal, Raw-Dust, Raw-Mud, Raw-White
16"x32"x10mm Field Tile	Raw-Coal, Raw-Dust, Raw-Mud, Raw-White
2"x24"x10mm Bullnose	Raw-Coal, Raw-Dust, Raw-Mud, Raw-White
12"x12"x10mm Mosaic	Raw-Coal, Raw-Dust, Raw-Mud, Raw-White

Special Order Sizes* (Nominal)

Dimensions	Available Colors
30x60 - 11 ³ / ₄ "x 23 ⁵ / ₈ " Field Tile	Raw-Coal, Raw-Dust, Raw-Mud, Raw-White (Struttarato)
60x60 - 23 ⁵ / ₈ "x 23 ⁵ / ₈ " Field Tile	Raw-Coal, Raw-Dust, Raw-Mud, Raw-White (Matte, Struttarato)
60x120 - 23 ⁵ / ₈ "x47 ¹ / ₈ " Field Tile	Raw-Coal, Raw-Dust, Raw-Mud, Raw-White
60x120 - 23 ⁵ / ₈ "x47 ¹ / ₈ " Field Tile	Raw-Coal, Raw-Dust, Raw-Mud, Raw-White
80x80 - 31 ¹ / ₂ "x31 ¹ / ₂ " Field Tile	Raw-Coal, Raw-Dust, Raw-Mud, Raw-White
80x180 - 31 ¹ / ₂ "x70 ³ / ₄ " Field Tile	Raw-Coal, Raw-Dust, Raw-Mud, Raw-White
21x40 - 8 ¹ / ₄ "x15 ⁵ / ₈ " Listello Sfalsato	Raw-Coal, Raw-Dust, Raw-Mud, Raw-White

* 12 - 14 Week Lead Time. Some additional trim and decor pieces are available.

Recycled Content

11% (Dust, White), 14% (Coal, Mud)
