




ASH CARBON CLAY FLINT



GRAPHITE GRAVEL SALT SAND



V2 Slight Variation

GLITCH

Regularity Characteristics

Technical Features	Norms	Required Standards	Value
Length & Width	ISO 10545-2	± 0,6%	Suitable for
Thickness		± 5,0%	Suitable for
Straightness of Sides		± 0,5%	Suitable for
Wedging		± 0,5%	Suitable for
Surface Flatness		± 0,5%	Suitable for

Structural Characteristics

Technical Features	Norms	Required Standards	Value
Water Absorption	ISO 10545-3	≤ 0,5%	Suitable for

Bulk Mechanical Characteristics

Technical Features	Norms	Required Standards	Value
Breaking Strength	ISO 10545-4	S ≥ 1300 N	S ≥ 1300 N
Modulus of Rupture		R ≥ 35 N/mm ²	R > 40 N/mm ²

Surface Mechanical Characteristics

Technical Features	Norms	Required Standards	Value
Scratch Resistance	UNE-67-101-1992	Not Provided by Manufacturer	Not Provided by Manufacturer
Resistance to Abrasion	ISO 10545-7	Not Provided by Manufacturer	Not Provided by Manufacturer

Thermal and Hygrometric Characteristics

Technical Features	Norms	Required Standards	Value
Coefficient of Thermal Linear Expansion	ISO 10545-8	Declared value	≈ 7x10 ⁻⁶ C ⁻¹
Thermal Shock Resistance	ISO 10545-9	Request	Resistant
Moisture expansion	ISO 10545-10	Declared value	Not Provided by Manufacturer
Resistance to Frost	ISO 10545-12	Request	Resistant

Safety Characteristics

Technical Features	Norms	Required Standards	Value
Dynamic Friction Coefficient	ANSI 137.1-2012 (D.C.O.F.)	≥ 0,42 WET	≥ 0,42 WET
Non-Slip Classification	DIN 51130	9 ≤ R ≤ 13	R10 Naturale R11 Antislip
	DIN 51097	A,B,C	A+B Naturale A+B+C Antislip

Chemical Characteristics

Technical Features	Norms	Required Standards	Value
Resistance to Chemicals	ISO 10545-13	According to Builder's Specification	Resistant
Colors Resistance to Light	DIN 51094	No Alteration	Suitable for
Resistance to Staining	ISO 10545-14	≥ Class 3	Suitable for

Stocked Sizes (Nominal)

Dimensions	Available Colors
12"x24"x9.5mm Field Tile	Ash, Carbon, Clay, Graphite, Salt, Sand
24"x48"x9.5mm Field Tile	Ash, Carbon, Clay, Graphite, Salt, Sand
24"x48"x9.5mm Fault	Ash, Carbon, Clay, Graphite, Salt, Sand
24"x48"x9.5mm Mix	Cold Mix, Warm Mix

Special Order Sizes* (Nominal)

Dimensions	Available Colors
30x60 - 12"x24"x9.5mm Field Tile	Flint, Gravel
60x60 - 24"x24"x9.5mm Field Tile	Ash, Carbon, Clay, Flint, Graphite, Gravel, Salt, Sand
60x60 - 24"x24"x9.5mm Antislip	Ash, Graphite, Gravel, Salt
60x120 - 24"x48"x9.5mm Field Tile	Flint, Gravel
90x90 - 36"x36"x9.5mm Field Tile	Ash, Graphite, Gravel, Salt
120x120 - 48"x48"x9.5mm Field Tile	Ash, Graphite, Gravel, Salt
60x120 - 24"x48"x9.5mm Fault	Flint, Gravel
60x60 - 24"x24"x20mm Grip	Ash, Gravel, Sand
5x60 - 2"x24"x9.5mm Bullnose	Ash, Carbon, Clay, Flint, Graphite, Gravel, Salt, Sand
30x120 - 13"x47"x9.5mm Gradino Costa Retta	Ash, Carbon, Clay, Flint, Graphite, Gravel, Salt, Sand
2x120 - 5/8"x47"x9.5mm Bacchetta Jolly	Ash, Carbon, Clay, Flint, Graphite, Gravel, Salt, Sand
2x2 - 5/8"x5/8"x9.5mm Unghia Jolly	Ash, Carbon, Clay, Flint, Graphite, Gravel, Salt, Sand

* 12 - 14 Week Lead Time.

Recycled Content

≥ 10%
