


ELEMENT



BLACK




GREY



STEEL GREY

WHITE



V1 Uniform Appearance

Regularity Characteristics

Technical Features	Norms	Required Standards	Value
Length & Width	ISO 10545-2	± 0,6%	Suitable for
Thickness		± 5,0%	Suitable for
Straightness of Sides		± 0,5%	Suitable for
Rectangularity		± 0,6%	Suitable for
Surface Flatness		± 0,5%	Suitable for

Structural Characteristics

Technical Features	Norms	Required Standards	Value
Water Absorption	ISO 10545-3	≤ 0,5%	Eb < 0,5%

Bulk Mechanical Characteristics

Technical Features	Norms	Required Standards	Value
Breaking Strength	ISO 10545-4	S ≥ 1300 N	S ≥ 1300 N
Modulus of Rupture		R ≥ 35 N/mm ²	R > 40 N/mm ²

Surface Mechanical Characteristics

Technical Features	Norms	Required Standards	Value
Scratch Resistance	UNE-67-101-1992	-	4
Resistance to Abrasion	ISO 10545-7	Not Provided by Manufacturer	4 (Grey & White) 3 (Black & Steel Grey)

Thermal and Hygrometric Characteristics

Technical Features	Norms	Required Standards	Value
Coefficient of Thermal Linear Expansion	ISO 10545-8	Declared value	Not Provided by Manufacturer
Thermal Shock Resistance	ISO 10545-9	Pass according to EN ISO 10545-1	Not Provided by Manufacturer
Moisture expansion	ISO 10545-10	Declared value	Not Provided by Manufacturer
Resistance to Frost	ISO 10545-12	Pass according to EN ISO 10545-1	Not Provided by Manufacturer

Safety Characteristics

Technical Features	Norms	Required Standards	Value
Dynamic Friction Coefficient	ANSI 137.1-2012 (D.C.O.F.)	≥ 0,42 WET	≥ 0,42 WET
Non-Slip Classification	DIN 51130	Basing on the Environment or on the Working Area	Not Provided by Manufacturer
	DIN 51097		Not Provided by Manufacturer











Chemical Characteristics

Technical Features	Norms	Required Standards	Value
Resistance to Household Chemicals and Swimming Pool Salts	ISO 10545-13	Class B	GA
Resistance to low concentrations of acids and alkalis		Declared Class	GLA
Resistance to High concentrations of acids and alkalis		Declared Class	GHA
Resistance to Staining	ISO 10545-14	Declared Class	5

Stocked Sizes (Nominal)

Dimensions	Available Colors
9"x11"x8mm Field Tile	Black, Grey, Steel Grey, White

Special Order Sizes* (Nominal)

Dimensions	Available Colors
25x25 - 10"x10"x8mm Octo 	Black, Grey, Steel Grey, White
8x25 - 3"x10"x8mm Field Tile 	Black, Grey, Steel Grey, White
20x50 - 8"x20"x8mm Liso 	White
33x33 - 13"x13"x8mm Sugar 	Black, White
33x33 - 13"x13"x8mm Basic 	Black, White
5x5 - 2"x2"x8mm Taco Element 	Black, Grey, Steel Grey, White
5x5 - 2"x2"x8mm Taco Argent Floral 	Black, Silver
5x5 - 2"x2"x8mm Taco Argent Geo 	Black, Silver
5x5 - 2"x2"x8mm Taco Argent Mini 	Black, Silver
5x5 - 2"x2"x8mm Taco Terni 	Black, Concept, White

* 12 - 14 Week Lead Time. Some additional sizes, finishes, trim and decor pieces are available.

Recycled Content

